



# Mastering Drupal 8's Twig

John Albin Wilkins  
November 24, 2017



Drupal™




Twig

<http://twig.sensiolabs.org/>

Twig for Template Designers

<https://twig.symfony.com/doc/1.x/templates.html>

# Drupal 8.4.2 has Twig 1.32.0



Why Twig?



# Modern Syntax

**Drupal 7:** `<?php print variable; ?>`

**Twig:** `{{ variable }}`



# Where's the performance hit?

```
<?php if ($is_true): ?> <b>TRUE!</b> <?php endif; ?>
```



PHP parser/compiler has to context switch

Twig  
compiles templates  
into PHP classes



# Twig syntax

`{{ variable }}`

`{# comment #}`

`{% command %}`



# Variable drilling

```
{{ variable.thing }}
```

```
{{ page.primary_menu }}
```

```
{{ comment.owner.anonymous }}
```

# This is how Twig resolves complex variables

```
<nav>{{ content.links }}</nav>
```

```
$content['links']
```

```
$content->links
```

```
$content->links()
```

```
$content->getLinks()
```

```
$content->isLinks()
```

```
null
```



Twig tries all these alternatives and uses the first one that exists.

# Some Drupal variables names are special

core/themes/bartik/bartik.theme

```
$variables['site_slogan']['#markup'] = ...
```

```
{{ site_slogan.#markup }}
```

← This doesn't work because of the # character

```
{{ site_slogan['#markup'] }}
```

```
{{ attribute(site_slogan, '#markup') }}
```

# Improving Twig performance

- Twig provides a PHP extension.
- This extension only implements the variable resolving logic.
- See [twig.sensiolabs.org/doc/installation.html#installing-the-c-extension](https://twig.sensiolabs.org/doc/installation.html#installing-the-c-extension)

EXPECTED  
PERFORMANCE  
INCREASE

**15%**

# Twig filters

(added by Twig)

\* `{{ variable|escape('html') }}`

\* `{{ variable|e('html') }}`

\* Also accepts: 'js', 'css', 'url', 'html\_attr'

\* `{{ variable|raw }}`

\* collections: |keys |first |last |length

\* `{{ variable|date('Y-m-d') }}`

`{{ 'now'|date(timezone=user.timezone) }}`

*Drupal  
auto-escapes  
by default!*

<http://twig.sensiolabs.org/doc/filters/index.html>

# Twig filters

(added by Drupal)

- \* `{{ variable|safe_join(', ') }}`
- \* `{{ variable|without('something') }}`
- \* `{{ variable|clean_class }}`  
`{{ variable|clean_id }}`
- \* `{{ variable|format_date('medium') }}`
- \* `{{ 'Some string'|t }}`

<https://www.drupal.org/node/2357633>

# Translation

- \* `{{ 'a string' |t }}`  
`{{ 'a string' |trans }}`
- \* `{% trans %}`  
    Submitted by `{{ author_name }}`  
    on `{{ date }}`  
`{% endtrans %}`

# Attribute object

- \* `{{ attributes.addClass('foo') }}`
- \* `{{ attributes.removeClass('bar') }}`
- \* `{% if attributes.hasClass('thing') %}`
- \* `{{ attributes.setAttribute('id', 'thing') }}`
- \* `{{ attributes.removeAttribute('id') }}`

[https://api.drupal.org/api/drupal/core!lib!Drupal!Core!  
Template!Attribute.php/class/Attribute/8](https://api.drupal.org/api/drupal/core!lib!Drupal!Core!Template!Attribute.php/class/Attribute/8)

# Control directives

\* `{% if thing %}`

`{% endif %}`

\* `{% for user in users %}`

`...`

`{% else %}`

`There is no spoon.`

`{% endfor %}`

\* `{% for item in collection if item.published %}`

# Control directives

```
{% for row in images|batch(3) %}  
  <div class="row">  
    {% for image in row %}  
      <div class="image">  
        <img src="" alt="" >  
      </div>  
    {% endfor %}  
  </div>  
{% endfor %}
```

# Extends

bartik/templates/region--header.html.twig:

```
{% extends "region.html.twig" %}
```

```
{% set attributes = attributes.addClass('clearfix') %}
```

classy/templates/layout/region.html.twig:

```
{%
```

```
  set classes = [
```

```
    'region',
```

```
    'region-' ~ region|clean_class,
```

```
  ]
```

```
%}
```

```
<div{{ attributes.addClass(classes) }}>
```

```
  {{ content }}
```

```
</div>
```

# Extends

classy/templates/block/block--system-branding-block.html.twig:

```
{% extends "block.html.twig" %}
{% block content %}
  <a href="{{ path('<front>') }}" rel="home">
    
  </a>
{% endblock %}
```

classy/templates/block/block.html.twig:

```
<div{{ attributes.addClass(classes) }}>
  <h2{{ title_attributes }}>{{ label }}</h2>
  {% block content %}
    {{ content }}
  {% endblock %}
</div>
```

# Include

- \* `{% include '@my_theme/grid_3.twig' %}`
- \* `{% include '@my_theme/grid_3.twig' with {  
    var1: "a new value",  
    var2: anotherVar,  
} only  
%}`

# Embed

```
* {% embed '@my_theme/grid_3.twig' %}  
  {% block column1 %}  
    ...block contents...  
  {% endblock %}  
{% endembed %}
```

# Debugging

- \* In sites/default, copy `default.services.yml` to `services.yml`.
- \* Look for these lines and change "false" to "true".  
`twig.config:`  
`debug: false`

<https://www.drupal.org/node/1906392>

# Libraries

## (adding CSS & JS)

**my\_theme.libraries.yml:**

breadcrumb:

css:

component:

components/breadcrumb/breadcrumb.css: {}

dependencies:

- my\_theme/visually-hidden

<https://www.drupal.org/node/2216195>

# What else?

Drupal 8 Theme Guide:  
[www.drupal.org/theme-guide/8](http://www.drupal.org/theme-guide/8)



**Drupal**<sup>TM</sup>